



Uniguest 800 Media Player.

Powerful 4K media player for all of your IPTV and Digital Signage requirements.

Key Features

Decodes MPEG2, H263, H264, H265, HEVC, VC-1, VP8, VP9, MVC, AV1, and live HLS, RTP and MPEG2-TS streams

Renders HTML5 webpages, HTML5 video tags, JPEGs, PNG, GIFs

Supports HDCP Professional content protection option

Works with 3rd Party Digital Signage HTML applications

Supports digital audio decoding

4K HDMI output

50GB of internal flash media storage

Uniguest 800 Media Player is a powerful solution for all IPTV, digital signage, and digital media delivery requirements.

The 800 unit can play out a wide variety of formats, including live network streams, locally stored video files, or files stored on a remote iVod server. It can also render HTML5 web pages, including those from a digital signage solution, and incorporate live and HDCP-protected streams and file-based video content.

What's in the box?	<ul style="list-style-type: none"> 800 Media Player unit External IR receiver HDMI cable CAT5E network cable Mains/DC power supply with UK, US, EU, AU adapters
Video	<p>Video Decoding</p> <ul style="list-style-type: none"> MPEG2, H263, H264, H265, HEVC, VC-1, VP8, VP9, MVC, AV1, and live HLS, RTP and MPEG2-TS streams <p>Video Output</p> <ul style="list-style-type: none"> HDMI - 2.1, Std. resolutions up to 2K (1080p50/60), 4K (2160p50/60)
Audio	<p>Audio Decoding</p> <ul style="list-style-type: none"> MPEG2-II, HE-AAC LC <p>Audio Input / Output</p> <ul style="list-style-type: none"> HDMI, PCM stereo and digital bitstream
Network	<ul style="list-style-type: none"> 2 x RJ-45 802.3 100/1000 Base T Auto MIDX jacks with integrated LEDs UDP, TCP, ARP, DHCP, ICMP, IGMP V2/V2, HTTP, HTTPS, SNMP, SMTP, NTP, RTSP Static or DHCP IP Address (default)
Ports	USB-C, USB 3.0, HDMI, External IR receiver
Power	<p>Power Supply:</p> <ul style="list-style-type: none"> Power over Ethernet 802.3at class 4 device AC mains adapter: 100-240VAC, 47-63Hz <p>Power Dissipation: 7W typical</p>
Physical	<p>Dimensions: 17cm x 9.5cm x 3.0cm</p> <p>Weight: 0.36Kg/0.8lbs</p> <p>Operating Temperature: 0 - 35°C; 32 - 95°F</p>
Approvals	<ul style="list-style-type: none"> FCC, CE, UKCA, RCM, TUV, CB and UL approved HEVC is covered by patents listed at patentlist.hevcadvance.com.