



Uniguest SP2.

Low cost 4K, PoE digital signage and IPTV media player for the professional AV industry.

Key Features

Supports both Tripleplay Digital Signage and IPTV Portal

Flawless playback of HD and 4K video, Full HD images & graphics and digital audio

Displays HTML5 widgets and animations

Optional RF hybrid remote for IPTV Portal

Ultra-thin design fits into tight spaces and streamlines serviceability

Power over Ethernet (PoE) for simple installation

32GB of built-in SD storage


Dual 1080p video support

The Uniguest SP2 is compatible with our Tripleplay IPTV and Digital Signage platform, delivering core AV industry requirements such as 4K video playback, RS232 control, full AES and VSecure encryption, and 32GB of storage for displaying evergreen fallback content.

| Media | |
|----------------------------------|---|
| Decoder | <ul style="list-style-type: none"> Single HD 1080p60 Dual 1080p60 with overlay support 4K60p video decoding |
| Video & HTML5 Engine | <ul style="list-style-type: none"> 1080p60 video 4Kp60 video HD image and motion graphics support Dual-zone static HTML OR Single-zone animated HTML Single HD video decode in single HTML zone HTML5 Single touch |
| Video Codecs | 4K: H.265/H.264 HD: H.265, H.264(MPEG-4, Part 10) MPEG-2 |
| 4K Video Containers | .ts, .mov, .mp4, .mkv |
| HD Video Containers | .ts, .mpg, .vob, .mov, .mp4, .m2ts |
| Graphics | Full HD Images and Graphics |
| Images | BMP, JPEG, PNG |
| Audio | MP2, MP3, AAC and WAV (AC3 is passed through) |
| HTML5 | .html, Chromium-based, CSS, JavaScript, WebGL |
| Security | |
| Digital Rights Management | Philips V-secure DRM |
| Encryption | AES128 Encryption |
| Physical | |
| Ports | <ul style="list-style-type: none"> 1 x HDMI output 2.0a 1 x USB Type A 1 x 3.5mm Audio out 1 x 3.5mm Serial port 1 x IR port 1 x 10/100/1000 Base Ethernet |
| Storage | Built-in micro-SD Slot with 32GB SD storage |
| Power | <ul style="list-style-type: none"> 12V/1.5A PoE IEEE 802.3af class 4 compliant Mains PSU selectable at order time |
| Dimensions | 205 x 186.5 x 19.2 mm |
| Weight | 600g (player only) |
| Mounting | Built-in wall mount bracket included |
| Network | |
| Ethernet | PoE IEEE 802.3af |
| Wireless | 802.11 ac |
| Accessories | |
| Optional | <ul style="list-style-type: none"> Multi-country mains power supply Wi-Fi module Remote screen controller (includes cable) Customised IR remote control (includes 3.5mm IR sensor) Customised RF multi-function remote control with dongle |

Uniguest SP2.

Dimensions and Mounting



Certifications

FCC United States of America
FCC Certified

CE European Economic Area
Conformité Européenne

UKCA United Kingdom
UK Conformity Assessed

 **Canada**
Industry Canada

 **Australia & New Zealand**
Regulatory Compliance Mark

 **India**
Bureau of Indian Standards

 **China**
China Quality Certification

 **South Korea**
Korean Certification

 **Taiwan**
BSMI Certified

 **California**
Proposition 65 Compliant

 **IECEE**
CB Safety Report