

Decoder	Single HD 1080p@60 Dual 1080p@60 with overlay support 4K@60p video encoding
Media Formats	Video Codecs for 4K content: H.265/H.264 Video Containers for 4K H.265/H.264 content: MPEG-2 Transport Streams Video Codecs for Full HD: H.265, H.264(MPEG-4, Part 10), MPEG-2, MPEG-1 Images: BMP, JPEG, PNG Audio: MP2, MP3, AAC, and WAV (AC3 is passed through)
Display Resolutions	4K resolutions 4096x2160, 3840x2160, 3840x600 Upscaling to 3840x2160x24/25/29.97/30p Native 1920x1200, 1920x1080x24/25/29.97/30/50/59.94/60p, 1920x1080x50/59.94/60i, 1600x1200x60p, 1440x1050x60/75p, 1440x900x60/75p, 1360x768x60p, 1280x1024x60/75p, 1280x960x60p, 1280x800x60p/75p, 1280x768x60p, 1280x720x50/59.94/60p, 1024x768x60p, 800x600x60/75p, 720x576x50p/50i, 720x480x59.94/60p/60i, 640x480x60p
Interfaces	USB High Speed Host Port (Type A) *1 3.5mm RS-232 Serial Port 3.5mm IR In/Out 3.5mm Audio Out (analogue -or- SPDIF digital, non-simultaneous) HDMI 2.0a Out Ethernet (Gigabit) Status LEDs Power, Error, Busy, Update Reset and Service Buttons
Security	Philips V-secure DRM *2 AES128 Encryption
Dimensions	Dimensions (W x H x D) 159.9 x 22 x 144.2mm or 6.3 x 0.87 x 5.7 in Weight 430g or 12 oz
Storage	Built-in micro SD Slot with 32GB SDXC storage
Power	Power 12V / 1.5A (18 Watts). PoE IEEE 802.3af class 4 compliant
Regulatory	Multi-country regulatory approvals
Options and Extras	RF Remote control with full TV database. Mains PSU selectable at order time. 100-250VAC 50-60Hz. Includes 4 international plugs for USA, UK, Australia and Europe. H: 63.5mm, W: 33mm, D: 69mm. 2.1m cable. AC3 decode license for non-AC3 displays. *3 <i>*1 Can be blanked and disabled. *2 Planned for Caveman 3.0. *3 AC3 decode for non-AC3 capable display devices is available as an added cost extra.</i>