



Uniguest SP2.

Low cost 4K, PoE digital signage and IPTV media player for the professional AV industry.

Key Features

Supports both Tripleplay Digital Signage and IPTV Portal

Flawless playback of HD and 4K video, Full HD images & graphics and digital audio

Displays HTML5 widgets and animations

Optional RF hybrid remote for IPTV Portal

Ultra-thin design fits into tight spaces and streamlines serviceability

Power over Ethernet (PoE) for simple installation

32GB of built-in SD storage

Dual 1080p video support

The Uniguest SP2 is compatible with our Tripleplay IPTV and Digital Signage platform, delivering core AV industry requirements such as 4K video playback, RS232 control, and full AES and VSecure encryption. There is also 32GB of SD storage built-in, enabling the player to display evergreen fallback content in the event of a network outage.

Capable of decoding two simultaneous video streams on the same device, this product is suited for advanced applications where highly dynamic content is a prerequisite, and excellent video quality is essential.

Media	
Video & HTML5 Engine	<ul style="list-style-type: none"> • 1080p60 video • 4Kp60 video • HD image and motion graphics support • Dual-zone static HTML OR Single-zone animated HTML • Single HD video decode in single HTML zone • HTML5 Single touch
Video Codecs	4K: H.265/H.264 HD: H.265, H.264(MPEG-4, Part 10) MPEG-2
4K Video Containers	.ts, .mov, .mp4, .mkv
HD Video Containers	.ts, .mpg, .vob, .mov, .mp4, .m2ts
Graphics	Full HD Images and Graphics
Images	BMP, JPEG, PNG
Audio	MP2, MP3, AAC and WAV (AC3 is passed through)
HTML5	.html, Chromium-based, CSS, JavaScript, WebGL
Security	
Digital Rights Management	Philips V-secure DRM
Encryption	AES128 Encryption
Physical	
Ports	<ul style="list-style-type: none"> • 1 x HDMI output 2.0a • 1 x USB Type A • 1 x 3.5mm Audio out • 1 x 3.5mm Serial port • 1 x IR port • 1 x 10/100 Base Ethernet
Storage	Built-in micro-SD Slot with 32GB SD storage
Power	<ul style="list-style-type: none"> • 12V/1.5A • PoE IEEE 802.3af class 4 compliant • Mains PSU selectable at order time
Dimensions	126.6 x 141.84 x 19.41 mm
Mounting	Built-in wall mount bracket included
Remote (optional)	RF Remote control with full TV database
Network	
Ethernet	PoE IEEE 802.3af
Wireless	802.11 ac